

(12) UK Patent Application (19) GB (11) 2 375 076 (13) A

(43) Date of A Publication 06.11.2002

(21) Application No 0111915.5

(22) Date of Filing 16.05.2001

(30) Priority Data

(31) 09846332 (32) 02.05.2001 (33) US

(71) Applicant(s)

Le Pointique International Limited
(Incorporated in USA - Washington)
1030 Industry Drive Suite 32c, Tukwila,
Washington 98188, United States of America

(72) Inventor(s)

Jonathon Chuang
Jackson Chiang

(74) Agent and/or Address for Service

Barker Brettell
138 Hagley Road, Edgbaston, BIRMINGHAM,
B16 9PW, United Kingdom

(51) INT CL⁷

B32B 5/18 , A61F 5/01 , B32B 3/24 3/30

(52) UK CL (Edition T)

B5N N0324 N0330 N0518 N175 N177 N180 N195 N196
N198 N207 N209 N21Y N223 N224 N226 N252 N255
N259 N264 N267 N27X N27Y N319 N323 N401 N418
N42X N42Y N46X N491 N492 N507 N508 N519 N52Y
N522 N53X N53Y N535 N536 N56Y N561 N563 N577
N593 N605 N648 N657 N66Y N661 N670 N695 N696
N784 N787
U1S S1044

(56) Documents Cited

GB 2312643 A




(58) Field of Search

UK CL (Edition S) B5N
INT CL⁷ A61F 5/01 , B32B 3/24 3/30 5/18
ONLINE: WPI, EPODOC, JAPIO

(54) Abstract Title

Material for elastic compression braces

(57) A flexible resilient composite material (100) used to manufacture elastic compression braces (20) comprises a centre layer (110) of elastic material having firstly a plurality of channels (140) formed in a first face of the centre layer, the channels intersecting to define a network and being capable of channeling away moisture and heat when the first face side is worn facing the wearer, and secondly a plurality of cuts (150) which expand to allow passage of moisture and air when the centre layer is stretched during use. Inner and outer fabric layers (130, 120) of a resiliently elastic porous fabric are attached to the opposite faces of the centre layer. The centre layer may be a closed cell foam. Silicone material may be applied to the brace to help cause the brace to stay in place on the wearer.



GB 2 375 076 A